## Aquaslab Permeable Block Paving

Data Sheet





Aquaslab offers a range of contemporary permeable paving slabs for use in pedestrian areas, they are available in 300mm x 450mm dimension and provides a clean, uncluttered design. The specially shaped block allows water to disperse to the lower levels, helping to prevent localised flooding.

## **Colours** For an accurate colour match please request a sample.

Charcoal



Natural





Red Brindle



Golden Brindle \*



Purbeck \*

## **Specification**

Block sizes (depth)	60mm		
450 x 300mm (blocks per pack)	84		
Coverage per pack (m <sup>2</sup> )	11.34		
Weight per pack (tonne)	1.49		
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa	Strength durability Class 1 Slip/skid resistance Satisfactory	<b>Finishes</b> Standard finish	<b>Applications</b> For use on pedestrian areas.

The Aquaslab permeable blocks are best used in combination with the Formpave Aquaflow® System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs.

\* Colour purposes only. † Special order.

Formpave

Tufthorn Avenue, Coleford Gloucestershire, GL16 8PR **Fax:** 01594 810 577

Tel: 01594 836 999 Web:

Email: sales@formpave.co.uk www.formpave.co.uk