

Forterra Building Products Limited 5 Grange Park Court, Roman Way Northampton, NN4 5EA

BS EN 1344:2013

ASHBOURNE RED MULTI PAVER

17

200 x 100 x 65 mm Clay pavers for external paving

Dimensional tolerances:

Range category: R1

Transverse breaking load:: Class T4

Slip / skid resistance: U3

Freeze thaw resistance: FP100

Abrasion resistance: A3

Reaction to fire: Class A1_{FC}

Dangerous Substances: NPD

See Also Declaration of Performance DOP/HANUK/BR/6150118

Declaration of Performance

DOP/HANUK/BR/6150316



The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

ASHBOURNE RED MULTI PAVER

- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: external paving
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited 5 Grange Park Court, Roman Way, Northampton, NN4 5EA

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: System 4

6 Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	200 x 100 x 65 mm Range Class R1	
Transverse Breaking Load	Class T4	
Slip / Skid Resistance	U3	EN 1344:2013
Freeze Thaw Resistance	FP100	
Abrasion Resistance	A3	
Reaction to Fire	Class A1 _{FC}	Commission Decision 2000/605/EC
Dangerous Subatances	NPD	EN 1344:2013

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert, Head of Quality // 4 July 2017



Forterra Building Products Limited 5 Grange Park Court, Roman Way Northampton, NN4 5EA

BS EN 1344:2013

SHERBOURNE RED PAVER

17

200 x 100 x 65 mm Clay pavers for external paving

Dimensional tolerances:

Range category: R1

Transverse breaking load:: Class T4

Slip / skid resistance: U3

Freeze thaw resistance: FP100

Abrasion resistance: A3

Reaction to fire: Class A1_{FC}

Dangerous Substances: NPD

See Also Declaration of Performance DOP/HANUK/BR/6150415

Declaration of Performance

DOP/HANUK/BR/6150415



The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

SHERBOURNE RED PAVER

- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).
- 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **external paving**
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited 5 Grange Park Court, Roman Way, Northampton, NN4 5EA

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

6. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	200 x 100 x 65 mm Range Class R1	
Transverse Breaking Load	Class T4	
Slip / Skid Resistance	U3	EN 1344:2013
Freeze Thaw Resistance	FP100	
Abrasion Resistance	A3	
Reaction to Fire	Class A1 _{FC}	Commission Decision 2000/605/EC
Dangerous Subatances	NPD	EN 1344:2013

7. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert, Head of Quality // 4 July 2017



Forterra Building Products Limited 5 Grange Park Court, Roman Way Northampton, NN4 5EA

BS EN 1344:2013

RUSHMERE BROWN PAVER

17

200 x 100 x 65 mm Clay pavers for external paving

Dimensional tolerances:

Range category: R1

Transverse breaking load:: Class T4

Slip / skid resistance: U3

Freeze thaw resistance: FP100

Abrasion resistance: A3

Reaction to fire: Class A1_{FC}

Dangerous Substances:

See Also Declaration of Performance DOP/HANUK/BR/6150316

Declaration of Performance

DOP/HANUK/BR/6150316



The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

8. Unique identification code of the product type:

RUSHMERE BROWN PAVER

- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).
- 10. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: external paving
- 11. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited 5 Grange Park Court, Roman Way, Northampton, NN4 5EA

12. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

13. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	200 x 100 x 65 mm Range Class R1	
Transverse Breaking Load	Class T4	
Slip / Skid Resistance	U3	EN 1344:2013
Freeze Thaw Resistance	FP100	
Abrasion Resistance	А3	
Reaction to Fire	Class A1 _{FC}	Commission Decision 2000/605/EC
Dangerous Subatances	NPD	EN 1344:2013

14. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert, Head of Quality // July 2017