

Declaration of Performance

DOP/STUR1001102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 100mm STUR1001102GR
20**

Turbo 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR1001102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR1001102GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR1151102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 115mm STUR1151102GR
20**

Turbo 115mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 115 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Turbo 115mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR1151102GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 115 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STUR1151102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STUR1251102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 125mm STUR1251102GR
20**

Turbo 125mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 125 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR1251102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 125mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STUR1251102GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 125 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR1301102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 130mm STUR1301102GR
20**

Turbo 130mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 130 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Turbo 130mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR1301102GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 130 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	470 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.10 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STUR1301102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STUR1401102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 140mm STUR1401102GR
20**

Turbo 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 140 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Turbo 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR1401102GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 140 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	470 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.10 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STUR1401102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STUR1501102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 150mm STUR1501102GR
20**

Turbo 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 150 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR1501102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 150mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR1501102GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 150 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR1901102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 190mm STUR1901102GR
20**

Turbo 190mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 190 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR1901102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 190mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STUR1901102GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 190 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR2001102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 200mm STUR2001102GR
20**

Turbo 200mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 200 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR2001102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 200mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STUR2001102GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 200 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR2151102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 215mm STUR2151102GR
20**

Turbo 215mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 215 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR2151102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 215mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STUR2151102GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 215 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR2651102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 265mm STUR2651102GR
20**

Turbo 265mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 265 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR2651102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 265mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STUR2651102GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 265 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity		
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR3001102GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 300mm STUR3001102GR
20**

Turbo 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Turbo 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR3001102GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	470 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.10 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STUR3001102GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SSHD0501103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 50mm SSHD0501103GR
20**

Shield 50mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 50 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD0501103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 50mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD0501103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 50 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD0751103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015
Shield 75mm SSHD0751103GR
20

Shield 75mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 75 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD0751103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 75mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SSHD0751103GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA
4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 75 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD0901103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 90mm SSHD0901103GR
20**

Shield 90mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 90 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD0901103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 90mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD0901103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 90 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1001103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 100mm SSHD1001103GR
20**

Shield 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1001103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1001103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1151103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 115mm SSHD1151103GR
20**

Shield 115mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 115 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1151103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 115mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **SSHD1151103GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 115 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1251103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 125mm SSHD1251103GR
20**

Shield 125mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 125 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1251103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 125mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1251103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 125 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1401103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 140mm SSHD1401103GR
20**

Shield 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 140 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1401103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1401103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 140 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1501103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 150mm SSHD1501103GR
20**

Shield 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 150 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1501103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 150mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1501103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 150 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1901103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 190mm SSHD1901103GR
20**

Shield 190mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 190 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1901103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 190mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1901103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 190 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD2001103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 200mm SSHD2001103GR
20**

Shield 200mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 200 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD2001103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 200mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD2001103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 200 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1001203GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 100 x 440 x 140mm SSHD1001203GR
20**

Shield 100 x 440 x 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Shield 100 x 440 x 140mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SSHD1001203GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SSHD1001203GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SSHD1001403GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 100 x 440 x 430mm SSHD1001403GR
20**

Shield 100 x 440 x 430mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 240 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1001403GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 100 x 440 x 430mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1001403GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 240 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SPWA1001104GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Party Wall 100mm SPWA1001104GR
20**

Party Wall 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Party Wall 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SPWA1001104GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	660 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.14 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SPWA1001104GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SPWA2151104GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Party Wall 215mm SPWA2151104GR
20**

Party Wall 215mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 215 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SPWA2151104GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Party Wall 215mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **SPWA2151104GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 215 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	660 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.14 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSB1002207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Brick 100mm SHSB1002207GR
20**

Hi-Strength Brick 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 100 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Brick 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSB1002207GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 100 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHSB1002207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHST1401607GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength 140mm SHST1401607GR
20**

Hi-Strength 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	530 (mm) x 440 (mm) x 145 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1401607GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1401607GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	530 x 440 x 145 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015
Hi-Strength 100mm SHST1001107GR
20

Hi-Strength 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:		
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1151107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015
Hi-Strength 115mm SHST1151107GR
20

Hi-Strength 115mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 115 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1151107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 115mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1151107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 115 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1251107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength 125mm SHST1251107GR
20**

Hi-Strength 125mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 125 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1251107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 125mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1251107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 125 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1401107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength 140mm SHST1401107GR
20**

Hi-Strength 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 140 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1401107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1401107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 140 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1501107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015
Hi-Strength 150mm SHST1501107GR
20

Hi-Strength 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 150 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1501107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 150mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SHST1501107GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA
4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 150 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1901107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength 190mm SHST1901107GR
20**

Hi-Strength 190mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 190 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1901107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 190mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1901107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 190 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST2001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength 200mm SHST2001107GR
20**

Hi-Strength 200mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 200 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST2001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 200mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST2001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 200 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST2151107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015
Hi-Strength 215mm SHST2151107GR
20

Hi-Strength 215mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 215 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST2151107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 215mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SHST2151107GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA
4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 215 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSPG1001104GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Paint Grade Smooth 100mm SSPG1001104GR
20**

Paint Grade Smooth 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Paint Grade Smooth 100mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SSPG1001104GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	660 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.14 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SSPG1001104GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SSPG1401104GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Paint Grade 140mm SSPG1401104GR
20**

Paint Grade 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 140 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Paint Grade 140mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SSPG1401104GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 140 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	660 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.14 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SSPG1401104GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SSPG1901104GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Paint Grade 190mm SSPG1901104GR
20**

Paint Grade 190mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 190 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 4.0 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSPG1901104GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Paint Grade 190mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **SSPG1901104GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 190 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 4.0 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	660 kg/m ³ As above	
Gross density:		
Configuration:	0.14 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSPG2001104GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Paint Grade 200mm SSPG2001104GR
20**

Paint Grade 200mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 200 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSPG2001104GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Paint Grade 200mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).
SSPG2001104GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 200 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 4.0 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	660 kg/m ³ As above	
Gross density:		
Configuration:	0.14 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS1001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 100mm SHSS1001107GR
20**

Hi-Strength Paint Grade 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSS1001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Paint Grade 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS1001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS1401107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 140mm SHSS1401107GR
20**

Hi-Strength Paint Grade 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 140 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSS1401107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Paint Grade 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS1401107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 140 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity		
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS1501107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 150mm SHSS1501107GR
20**

Hi-Strength Paint Grade 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 150 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSS1501107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Paint Grade 150mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS1501107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 150 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS1901107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 190mm SHSS1901107GR
20**

Hi-Strength Paint Grade 190mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 190 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Paint Grade 190mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS1901107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 190 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHSS1901107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHSS2001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 200mm SHSS2001107GR
20**

Hi-Strength Paint Grade 200mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 200 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSS2001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Paint Grade 200mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS2001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 200 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS2151107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 215mm SHSS2151107GR
20**

Hi-Strength Paint Grade 215mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 215 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Paint Grade 215mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS2151107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 215 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHSS2151107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STRE2551103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 255mm STRE2551103GR
20**

Trenchblock 255mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 255 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STRE2551103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock 255mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STRE2551103GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 255 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STRE2751103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 275mm STRE2751103GR
20**

Trenchblock 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STRE2751103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock 275mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STRE2751103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	Resistant to Freeze Thaw	
Durability Against Freeze Thaw	NPD	
Dangerous Substances		

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STRE3001103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 300mm STRE3001103GR
20**

Trenchblock 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STRE3001103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STRE3001103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STRE3551103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 355mm STRE3551103GR
20**

Trenchblock 355mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 355 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STRE3551103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock 355mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STRE3551103GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 355 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STRE275120GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 275mm STRE275120GR
20**

Trenchblock 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock 275mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STRE275120GR**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STRE275120GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STRE300120GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 300mm STRE300120GR
20**

Trenchblock 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [A _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STRE300120GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [A _{10,dry unit} , S2]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STRE300120GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STTG2551103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 255mm STTG2551103GR
20**

Trenchblock T&G 255mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 255 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock T&G 255mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

STTG2551103GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 255 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STTG2551103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STTG2751103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 275mm STTG2751103GR
20**

Trenchblock T&G 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock T&G 275mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

STTG2751103GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STTG2751103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STTG3001103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 300mm STTG3001103GR
20**

Trenchblock T&G 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock T&G 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STTG3001103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STTG3001103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STTG3551103GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 355mm STTG3551103GR
20**

Trenchblock T&G 355mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 355 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock T&G 355mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STTG3551103GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 355 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STTG3551103GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHST2551107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 255mm SHST2551107GR
20**

Hi-Strength Trench 255mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 255 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST2551107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Trench 255mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST2551107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 255 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST2751107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 275mm SHST2751107GR
20**

Hi-Strength Trench 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Trench 275mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SHST2751107GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHST2751107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHST3001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 300mm SHST3001107GR
20**

Hi-Strength Trench 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST3001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Trench 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST3001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST3551107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 355mm SHST3551107GR
20**

Hi-Strength Trench 355mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 355 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Trench 355mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST3551107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 355 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHST3551107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHST2751207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 140 x 275mm SHST2751207GR
20**

Hi-Strength Trench 140 x 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Trench 140 x 275mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST2751207GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHST2751207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHST3001207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 140 x 300mm SHST3001207GR
20**

Hi-Strength Trench 140 x 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST3001207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Trench 140 x 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST3001207GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST3551207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 140 x 355mm SHST3551207GR
20**

Hi-Strength Trench 140 x 355mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 355 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength Trench 140 x 355mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SHST3551207GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 355 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHST3551207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHTG2551107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength T&G 255mm SHTG2551107GR
20**

Hi-Strength T&G 255mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 255 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength T&G 255mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHTG2551107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 255 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHTG2551107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHTG2751107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength T&G 275mm SHTG2751107GR
20**

Hi-Strength T&G 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Hi-Strength T&G 275mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SHTG2751107GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA
4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHTG2751107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHTG3001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength T&G 300mm SHTG3001107GR
20**

Hi-Strength T&G 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHTG3001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength T&G 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHTG3001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	Resistant to Freeze Thaw	
Durability Against Freeze Thaw	NPD	
Dangerous Substances		

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHTG3551107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength T&G 355mm SHTG3551107GR
20**

Hi-Strength T&G 355mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 355 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHTG3551107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength T&G 355mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHTG3551107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 355 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSB1001207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**H/S Coursing Block 100mm SHSB1001207GR
20**

H/S Coursing Block 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

H/S Coursing Block 100mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SHSB1001207GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHSB1001207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHSB1151207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**H/S Coursing Block 115mm SHSB1151207GR
20**

H/S Coursing Block 115mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 115 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSB1151207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

H/S Coursing Block 115mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSB1151207GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 115 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSB1401207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**H/S Coursing Block 140mm SHSB1401207GR
20**

H/S Coursing Block 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 140 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

H/S Coursing Block 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSB1401207GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 140 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SHSB1401207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SHSB1501207GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**H/S Coursing Block 150mm SHSB1501207GR
20**

H/S Coursing Block 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 150 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSB1501207GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

H/S Coursing Block 150mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSB1501207GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 150 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SBRI1002203GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Bricks 100mm SBRI1002203GR
20**

Bricks 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 100 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Bricks 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SBRI1002203GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 100 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		
Gross density: Configuration:	600 kg/m ³ As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SBRI1002203GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SBRI1152203GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Bricks 115mm SBRI1152203GR
20**

Bricks 115mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 115 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SBRI1152203GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Bricks 115mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SBRI1152203GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 115 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SBRI1252203GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Bricks 125mm SBRI1252203GR
20**

Bricks 125mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 125 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SBRI1252203GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Bricks 125mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SBRI1252203GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 125 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SBRI1402203GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Bricks 140mm SBRI1402203GR
20**

Bricks 140mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 140 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SBRI1402203GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Bricks 140mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SBRI1402203GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 140 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SBRI1502203GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Bricks 150mm SBRI1502203GR
20**

Bricks 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 150 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SBRI1502203GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Bricks 150mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SBRI1502203GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 150 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR1001102VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 100mm STUR1001102VO
20**

Turbo 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR1001102VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STUR1001102VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STUR1301102VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Turbo 130mm STUR1301102VO
20**

Turbo 130mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 130 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	470 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.10 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STUR1301102VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Turbo 130mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STUR1301102VO**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 130 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 2.9 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	470 kg/m ³ As above	
Gross density:		
Configuration:	0.10 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD0901103VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 90mm SSHD0901103VO
20**

Shield 90mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 90 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD0901103VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 90mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD0901103VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 90 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSHD1001103VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 100mm SSHD1001103VO
20**

Shield 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1001103VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1001103VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	600 kg/m ³ As above	
Gross density:		
Configuration:	0.13 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST1001107VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength 100mm SHST1001107VO
20**

Hi-Strength 100mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [± bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST1001107VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength 100mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST1001107VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [± bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS1501107VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 150mm SHSS1501107VO
20**

Hi-Strength Paint Grade 150mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 150 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSS1501107VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Paint Grade 150mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS1501107VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 150 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSS2001107VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Paint Grade 200mm SHSS2001107VO
20**

Hi-Strength Paint Grade 200mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 200 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSS2001107VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Paint Grade 200mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSS2001107VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 200 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STRE2551103VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 255mm STRE2551103VO
20**

Trenchblock 255mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 255 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STRE2551103VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock 255mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STRE2551103VO**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 255 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	EN 771-4: 2011 + A1:2015
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STRE275120VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 275mm STRE275120VO
20**

Trenchblock 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [A _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock 275mm autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

STRE275120VO
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4
5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [A _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STRE275120VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STRE300120VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock 300mm STRE300120VO
20**

Trenchblock 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

1. Unique identification code of the product type:

Trenchblock 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). **STRE300120VO**

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STRE300120VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STTG2751103VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 275mm STTG2751103VO
20**

Trenchblock T&G 275mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 275 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STTG2751103VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock T&G 275mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STTG2751103VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 275 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/STTG3001103VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 300mm STTG3001103VO
20**

Trenchblock T&G 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/STTG3001103VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Trenchblock T&G 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). STTG3001103VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST3001107VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 300mm SHST3001107VO
20**

Hi-Strength Trench 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST3001107VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Trench 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST3001107VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHST3551207VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength Trench 140 x 355mm SHST3551207VO
20**

Hi-Strength Trench 140 x 355mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 355 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHST3551207VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength Trench 140 x 355mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHST3551207VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 355 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	Resistant to Freeze Thaw	
Durability Against Freeze Thaw	NPD	
Dangerous Substances		

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHTG3001107VO



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Hi-Strength T&G 300mm SHTG3001107VO
20**

Hi-Strength T&G 300mm autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHTG3001107VO

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Hi-Strength T&G 300mm autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHTG3001107VO

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit} , S2]	
Equivalent Thermal Conductivity	Resistant to Freeze Thaw	
Durability Against Freeze Thaw	NPD	
Dangerous Substances		

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SHSB1001307GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**140mm High Coursing Block 7.3N SHSB1001307GR
24**

140mm High Coursing Block 7.3N autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SHSB1001307GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

140mm High Coursing Block 7.3N autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SHSB1001307GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 7.3 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability	Nominal 0.50 mm/m	
Moisture Movement:		
Shear Bond Strength	0.15 N/mm ²	
Fixed value:		
Flexural Bond Strength:	NPD	Commission Decision 2000/605/EC
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	EN 771-4: 2011 + A1:2015
Water Vapour Permeability	5/10	
Fixed Value:		
Direct Airborne Sound Insulation	730 kg/m ³ As above	
Gross density:		
Configuration:	0.16 W/m.K [λ _{10,dry unit, S2}]	
Equivalent Thermal Conductivity	NPD	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SSCB1001336GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**140mm High Coursing Block 3.6N SSCB1001336GR
24**

140mm High Coursing Block 3.6N autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 140 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	600 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.13 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

1. Unique identification code of the product type:

140mm High Coursing Block 3.6N autoclaved aerated concrete masonry units
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).

SSCB1001336GR
1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 140 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	600 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.13 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SSCB1001336GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/STTG3001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Trenchblock T&G 300mm High Density STTG3001107GR
24**

Trenchblock T&G 300mm High Density autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 300 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit, S2}]
Durability against freeze-thaw:	Resistant to Freeze Thaw
Dangerous Substances:	NPD

- Unique identification code of the product type:
Trenchblock T&G 300mm High Density autoclaved aerated concrete masonry units
- Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4).
STTG3001107GR
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):
Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 300 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit, S2}]	
Durability Against Freeze Thaw	Resistant to Freeze Thaw	
Dangerous Substances	NPD	

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/STTG3001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

Declaration of Performance

DOP/SSHD1001107GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

**Shield 100mm High Density SSHD1001107GR
24**

Shield 100mm High Density autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	440 (mm) x 100 (mm) x 215 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	730 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.16 W/m.K [λ _{10,dry unit} , S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

See Also Declaration of Performance DOP/SSHD1001107GR

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Shield 100mm High Density autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SSHD1001107GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	440 x 100 x 215 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability		
Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength		Commission Decision 2000/605/EC
Fixed value:	0.15 N/mm ²	
Flexural Bond Strength:	NPD	EN 771-4: 2011 + A1:2015
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability		
Fixed Value:	5/10	
Direct Airborne Sound Insulation		EN 771-4: 2011 + A1:2015
Gross density:	730 kg/m ³	
Configuration:	As above	
Equivalent Thermal Conductivity	0.16 W/m.K [λ _{10,dry unit} , S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

Declaration of Performance

DOP/SBRI1002236GR



Forterra Building Products Limited
5 Grange Park Court, Roman Way
Northampton, NN4 5EA

BS EN 771-4:2011 + A1:2015

Bricks 100mm 3.6N SBRI1002236GR
24

Bricks 100mm 3.6N autoclaved aerated concrete masonry units

Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions

Dimensions:	215 (mm) x 100 (mm) x 65 (mm)
Dimensional tolerances:	GPLM (unless stated otherwise on the delivery ticket)
Configuration:	Solid
Compressive strength:	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]
Dimension Stability:	
Moisture Movement:	Nominal 0.50 mm/m
Shear Bond Strength:	
Fixed value:	0.15 N/mm ²
Flexural Bond Strength:	NPD
Reaction to fire:	Euroclass A1
Water Absorption:	NPD
Water vapour diffusion coefficient :	
Fixed Value:	5/10
Direct airborne sound insulation:	
Gross density:	660 kg/m ³
Configuration:	As Above
Thermal conductivity:	0.14 W/m.K [$\lambda_{10,dry,unit}$, S2]
Durability against freeze-thaw:	NPD
Dangerous Substances:	NPD

The performance of the product identified above is in conformity with the declared values, when installed in accordance with the manufacturer's instructions and general purpose or lightweight mortars.

1. Unique identification code of the product type:

Bricks 100mm 3.6N autoclaved aerated concrete masonry units

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4). SBRI1002236GR

1. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Loadbearing and non-loadbearing applications in all forms of walling including single leaf, cavity and partitions**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Forterra Building Products Limited
5 Grange Park Court, Roman Way,
Northampton, NN4 5EA

4. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**

5. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions and Dimensional Tolerance	215 x 100 x 65 mm GPLM (unless stated otherwise on the delivery ticket)	EN 771-4: 2011 + A1:2015
Configuration	Solid	
Compressive Strength	Mean 3.6 N/mm ² [⊥ bed face, whole unit]. [Cat II]	
Dimensional Stability Moisture Movement:	Nominal 0.50 mm/m	
Shear Bond Strength Fixed value:	0.15 N/mm ²	Commission Decision 2000/605/EC
Flexural Bond Strength:	NPD	
Reaction to Fire	Euroclass A1	
Water Absorption	NPD	
Water Vapour Permeability Fixed Value:	5/10	EN 771-4: 2011 + A1:2015
Direct Airborne Sound Insulation		
Gross density: Configuration:	660 kg/m ³ As above	
Equivalent Thermal Conductivity	0.14 W/m.K [$\lambda_{10,dry,unit}$, S2]	
Durability Against Freeze Thaw	NPD	
Dangerous Substances	NPD	

6. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

A C Cuthbert,
Quality Control Manager
Place of Signing: Northampton, UK

15 April 2025

See Also Declaration of Performance DOP/SBRI1002236GR